

Specifications:






TECHNOLOGY	With P4x SPREADERS
Nominal input:	43.2 VDC
Water rating:	IP66
Rotating Powerhead angle:	61°
Weight without battery or tool attachmen	nt: 31.5 lbs (14.3 kg)
Weight with battery and tool attachment	: 45 lbs (20.4 kg)
Width:	10.4 in. (264mm)
Height:	10.3 in. (262mm)
Length without tool attachment:	16 in. (406mm)
Length with tool attachment:	23.8 in. (604mm)
Length with tool attachment rotated:	18 in. (457mm)
Spreading distance:	16 in. (406mm)
Forces at tips (1 inch from end):	9,200 to 15,000 lbf (40.9 to 66.7 kN)
Forces at base of removable tips:	13,800 to 38,400 lbf (61.4 to 170.8 kN)
Forces at base of arm teeth:	23,300 to 175,000 lbf (103.6 to 778.4 kN)

<b>=D</b>	With P4w CUTTER
Nominal input:	43.2 VDC
Water rating:	IP66
Rotating Powerhead angle:	61°
Weight without battery or tool attachment:	31.5 lbs (14.3 kg)
Weight with battery and tool attachment:	48.5 lbs (22 kg)
Width:	10.4 in. (264mm)
Height:	10.3 in. (262mm)
Length without tool attachment:	16 in. (406mm)
Length with tool attachment:	23.6 in. (604mm)
Length with tool attachment rotated:	20 in. (508mm)
Cutter opening:	5.8 in (147mm)
Max cutting force:	115,000 lbf (510 kN)

## P4 Kit Components & Accessories:







Battery



EDD 10X Battery



EDD Powe Adapter



Aircraft Spreader Tips



LED Light w/ mounting strap

## THE PIONEER IN BATTERY-POWERED RESCUE TOOLS



A NEW ERA BEGINS IN **BATTERY-POWERED** RESCUE TOOLS **BEYOND HYDRAULICS** INTRODUCING THE NEW **POWERHAWK**\* RESCUE TOOL SYSTEMS In Partnership with RESQUEC

Copyright All of the information and material inclusive of text, images, logos, product names is either the property of, or used with permission by Power Hawk Technologies, Inc (PHT). The information may not be distributed, modified, displayed, reproduced –in whole or in part – without prior written permission by PHT.

Trademarks POWER HAWK® and its logo are registered trademarks of Power Hawk Technologies, Inc. RESOTEC® and its logo are registered trademarks prior to the part – without prior written permission by PHT.

Disclaimer All information herein was carefully gathered and examined, however, PHT cannot be held responsible for mistakes or incompleteness of content. PHT may change or modify parts at any time without notification and accepts no liability for the consequences of activities undertaken based on the content.





**NO HYDRAULICS** 

**MEANS...** 

- High-Efficiency Direct Power and VERY LONG BATTERY RUN TIMES
- NO captured hydraulic fluid to heat up rapidly, leak and reduce output power

The P4 unites the innovations of POWER HAWK's aerospace gear technology with RESQTEC's latest Electronic Direct Drive (EDD) motor and lithium battery technology, resulting in a super compact and self-contained battery powered rescue tool that delivers enormous spreading and cutting power for getting jobs done! Unmatched VERSATILITY and POWER has soared to new heights. Come and experience it for yourself!



The rotating Powerhead of the P4 enables spreading and cutting in tight spots and around corners. In other words, places other rescue tools just cannot go!



Patented Rotating Powerhead









Quick change Long lasting Battery with charge indicator and on/off switch



Accessory: 10x battery backpack

The P4 is powered by the latest in Lithium Ion battery technology and conforms to IEC62133 safety standards and the UN 38.3 shipping requirements for lithium batteries. The motor technology leveraged in EDD produces a staggering 1.4kW, similar to a small gasoline engine currently used in hydraulic pumps.